

# VIASENSOR

A ▼ QED COMPANY

**CO<sub>2</sub> INDOOR AIR QUALITY  
ANALYZER  
G150**

**AIR QUALITY  
CHECK ANALYZER**



G150

**CO<sub>2</sub> analyzer** designed to **monitor CO<sub>2</sub>**  
for all **Indoor Air Quality (IAQ)** applications.

This unit has been developed to incorporate the latest technology and specification requirements to provide the user with a fast, simple-to-use and accurate piece of environmental field equipment.

- ❖ **Ideal for Indoor Air Quality (IAQ) applications**
- ❖ **Quick verification of CO<sub>2</sub> levels**
- ❖ **Built in gas moisture removal**

# VIASENSOR

[www.viasensor.com](http://www.viasensor.com)

2355 Bishop Circle West - Dexter, MI. 48130 • Phone +1 (909) 783-9472 • +1 (855) VIASENSOR • Fax +1 (909) 825-0591

# VIASENSOR

A QED COMPANY

## CO<sub>2</sub> INDOOR AIR QUALITY ANALYZER G150



AIR QUALITY CHECK ANALYZER

### Features

- CO<sub>2</sub> 0 – 10,000 ppm
- Options for:
  - O<sub>2</sub> 0 – 100%
  - Dual temperature probes 32°F – 122°F (0°C – 50°C)
  - Humidity Sensor 0 – 100%
  - Data storage and download

### Applications

- General IAQ
- Site Audits
- Laboratories
- Medical

### Key Benefits

- High accuracy on CO<sub>2</sub> readings
- Quick verification of CO<sub>2</sub> levels for site audits
- Time saving with dual temperature probes
- Data logging for long-term application
- Easy to read large well-lit display
- Built in gas moisture removal

### TECHNICAL SPECIFICATIONS:

#### Gas Ranges

Gases Measured	CO <sub>2</sub>	By custom dual wavelength infra-red sensor with reference channel
	O <sub>2</sub> (Optional)	By internal electrochemical cell
Oxygen cell lifetime	Approximately 3 years in air	
Range	CO <sub>2</sub>	0-10,000ppm
	O <sub>2</sub>	0-100%
Measurement Accuracy*	Gas	
	CO <sub>2</sub>	± 1.5% of range after user calibration (typically ± 10ppm at 500ppm CO <sub>2</sub> , after user calibration)
	O <sub>2</sub>	± 1.0% of range after user calibration
Response time, T <sup>90</sup>	CO <sub>2</sub>	≤20 seconds
	O <sub>2</sub>	≤60 seconds

\* plus accuracy of calibration gas used

#### Facilities

Temperature (Optional)	X2 using optional probes, range 32°F to 122°F (0°C to +50°C)
Temperature accuracy, typical	±0.2°C
Barometric pressure	800-1,200 mbar
RH measurement (Optional)	RH Probe 0-100% RH non condensing
RH accuracy	±1.5% RH across the range
Visual and audible alarm	User selectable CO <sub>2</sub> and O <sub>2</sub> alarm levels
Communications	USB type B mini-connect, HID device class
Data Storage	1,000 reading sets + 270 events

#### Environmental Conditions

Operating temperature	32°F - 102°F (0°C - 50°C)
Relative humidity	0 - 95% non condensing (RH Probe 0-100% non condensing)
Barometric pressure	±201 H <sub>2</sub> O from calibration pressure, (±500mbar)

#### Pump

Flow	100cc/min typically
------	---------------------

#### Power Supply

Battery type	Li Ion
Battery life	10 Hours (8 hours with pump)
Battery lifetime	>300 Cycles
Battery charger	5v DC external power supply and internal charging circuit
Charge time	3 Hours
Alternative power	USB connector DC power supply

#### Physical

Weight	1.1 lbs (495 grams)
Size	L 6.5 in, W 3.9 in, D 2.2 in (L 165mm, W100mm, D55mm)
Case Material	ABS / Polypropylene with Silicone Rubber Inserts
Keys	17 Resin capped Silicone rubber keys
Display	Liquid crystal display, 128 x 64 pixel With RGB LED back-light
Gas sample filters	Built-in gas dryer tube to remove moisture User replaceable PTFE water trap filter

#### Note:

Due to VIASENSOR'S continuous program of improvement, this specification is subject to change without prior notice.

VIASENSOR  
2355 Bishop Circle West  
Dexter, MI. 48130  
Phone +1 (909) 783-9472  
Fax +1 (909) 825-0591